

DESIGN FEATURES: Gita make 'SD' pumps are horizontal split casing, horizontal shaft pumps with double suction impeller. Suction and delivery branches are cast integral with lower half casing. Inspection is easy and quick by removing upper casing and rotor assembly.

RANGES OF SIZE:- Available from 80mm suction to 750mm suction sizes. Head range from 5 to 80 meters and capacity from 15 to 7000 Cu.M. per hour.

CONSTRICTION DETAIL:

CASING:- Close grained cast iron, split horizontally, delivery and suction branches cast with lower half casing. By removing top half, rotor assembly can be removed for inspection.

IMPELLER:- Double Suction, closed impeller, machined all over, internal passages hand finished for high efficiency, dynamically balanced after mounting on shaft.

SHAFT:- Sturdily designed for maximum load with adequate safety factor, ground finished and protected from liquid by sleeves.

IMPELLER NECK RINGS:- Renewable neck rings are provided to keep suction improved, secured in lower half casing by spigot joint.


BEARINGS:- Antifriction grease lubricated, heavy duty ball bearings capable of carrying heavy loads in either direction for continuous operation.

FLANGES:- Drilled as per BS-10 table D or other standard as per customer's option.


ROTATION:- Clockwise, looking from drive end or as per customer's option

CROSS SECTIONAL VIEW OF "SD" PUMPS

NI.	
No.	Part Name Qty. Per Reqd. Pum CASING (LOWER HAFT)
1B	CASING (LOWER HAFT) CASING (UPPER HALF)
2	IMPELLER
6	SHAFT (PUMP)
7	WEAR RING IMPELLER
13	GLAND PACKING
14	SHAFT SLEEVE
16	BEARING (IN BOARD)
17	GLAND
18	BEARING (OUT BOARD)
20A	SHAFT SLEEVE NUT
20B	SHAFT SLEEVE NUT
22	BEARING LOCK NUT
29	CAGE RING
31	BEARING HOUSING (IN BOARD)
32	IMPELLER KEY
33	BEARING HOUSING (OUT BOARD)
35	BEARING COVER (IN BOARD)
37	BEARING COVER (OUT BOARD)
40	DEFLECTOR
41	BEARING HOUSING CAP (IN BOARD)
43	BEARING HOUSING CAP (OUT BOARD)
44	COUPLING (PUMP HALL)
46	COUPLING KEY
50	COUPLING LOCK NUT
63	STUFFING BOX BUSHING
78	BEARING SPACER
123	BEARING HOUSING END COVER GREASE CUP
	GLAND SEALING PIPE
175	
176	SLEEVE SPACER
1/0	SLEEVE SPACEK



PERFORMANCE CHARACTERISTICS 1450 RPM MODEL "SD"





GITA PUMPS INDIA PVT. LTD.

H.O: POST BOX 32,GITA COMPOUND, PAPER MILL ROAD, SAHARANPUR - 247001 WORKS: VILL-CHHAJPURA, P.O.: KAILASHPUR, DEHRADUN ROAD, SAHARANPUR PHONE: 0132-2786540, 2786541(FAX), 2786509, 9639013245, Upto 56, 9639013246, Email: sales@gitapumps.com Website: www.gitapumps.com